

# Technical data sheet

Profile rail, 17 mm slot, perforated, black

Item number: 1104269



Middle C profile rail for cable routing, in connection with clamp clips with hammer-head foot Can also be used as a suspended construction for cable tray systems.



- St** Steel
- P135** PES135 - Polyester

| Master data                        |                              |  |
|------------------------------------|------------------------------|--|
| Item number                        | 1104269                      |  |
| Type                               | CML3518P0200 SW              |  |
| Description 1                      | Profile rail                 |  |
| Description 2                      | perforated, slot width 17 mm |  |
| Manufacturer                       | OBO                          |  |
| Dimension                          | 200x35x18                    |  |
| Colour                             | Jet black; RAL 9005          |  |
| Material                           | Steel                        |  |
| Surface                            | PES135 - Polyester           |  |
| Surface standard                   |                              |  |
| Smallest sales unit                | 25                           |  |
| Unit of quantity                   | Piece                        |  |
| Weight                             | 15 kg                        |  |
| Weight unit                        | kg/100 pc.                   |  |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,3857 kg CO2e / 1 Piece     |  |


# Technical data sheet

Profile rail, 17 mm slot, perforated, black

Item number: 1104269



## Dimensions



|        |        |
|--------|--------|
| Length | 200 mm |
| Width  | 35 mm  |
| Height | 18 mm  |

## Technical data

|                               |                      |
|-------------------------------|----------------------|
| Breakable                     | no                   |
| Type of perforation           | Perforated back      |
| Version for                   | Single profile       |
| Drill hole spacing, centre    | 25 mm                |
| Maintain electrical functions | yes                  |
| Material thickness            | 1.25 mm              |
| With perforation              | yes                  |
| With toothing                 | no                   |
| Profile shape                 | C profile            |
| ROHS-conformant               | yes                  |
| Rustproof steel, pickled      | no                   |
| Slot width                    | 17 mm                |
| Static value I <sub>y</sub>   | 0.41 cm <sup>4</sup> |
| Static value I <sub>z</sub>   | 1.81 cm <sup>4</sup> |
| Static value W <sub>y</sub>   | 0.41 cm <sup>3</sup> |
| Static value W <sub>z</sub>   | 1.03 cm <sup>3</sup> |